


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau014334PC  
CN12703091

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : G02B 6/26, 6/28		A1	(11) International Publication Number: WO 93/13437
			(43) International Publication Date: 8 July 1993 (08.07.93)
(21) International Application Number: PCT/US92/07247 (22) International Filing Date: 27 August 1992 (27.08.92) (30) Priority data: 815,963 2 January 1992 (02.01.92) US (71) Applicant: ADC TELECOMMUNICATIONS, INC. [US/ US]; 4900 West 78th Street, Minneapolis, MN 55435 (US). (72) Inventors: EMMONS, David, J. ; 670 Windemere Curve, Plymouth, MN 55443 (US). LU, Liang-Ju ; 15815 Scenic Heights Road, Eden Prairie, MN 55344 (US).			(74) Agent: SCHUMANN, Michael, D.; Merchant, Gould, Smith, Edell, Welter & Schmidt, 3100 Norwest Center, 90 South Seventh Street, Minneapolis, MN 55402 (US). (81) Designated States: AT, AU, BB, BG, BR, CA, CH, CS, DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, PL, RO, RU, SD, SE, UA, Euro- pean patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG):  Published With international search report.

(54) Title: OVERLAPPING FUSION ATTENUATOR



## (57) Abstract

A method for fabricating an optical attenuator from first and second optical fibers includes placing the fibers in closely spaced overlapped relation to define an overlapped portion of the fibers. Energy is initially applied to the overlapped portion to at least partially fuse the first and second fibers at the overlapped portion.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

## OVERLAPPING FUSION ATTENUATOR

I. BACKGROUND OF THE INVENTION5 1. Field of the Invention

This invention pertains to a fiber optic attenuator for use in attenuating a signal transmitted over optical fibers.

10

2. Description of the Prior Art

The use of in-line optical fiber attenuators is well known. Examples of such are shown in U.S. Patent No. 4,529,262; U.S. Patent No. 4,557,557; and U.S. Patent  
15 No. 4,557,556.

It is desirable to provide for a method for fabricating a low cost optical fiber attenuator. Furthermore, such a method should be susceptible to producing a variety of attenuators which will produce a  
20 variety of desired signal losses. It is an object of the present invention to provide a method of fabricating a low cost attenuator which is susceptible to fabricating attenuators of a wide variety of signal losses.

25

II. SUMMARY OF THE INVENTION

According to a preferred embodiment of the present invention, a method is disclosed for fabricating an optical attenuator from at least a first and second  
30 optical fiber. The method includes the steps of placing the first and second fibers in closely spaced overlapping relation to define an overlapped portion of the fibers. Energy is applied to the overlapped portion to at least partially fuse the first and second fibers  
35 at the overlapped portion.

### III. BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a sectional view of two fibers disposed for fusion according to the method of the present invention;

5 Fig. 2 is a view of the fibers of Fig. 1 after application of energy to the overlapped portion of the fibers;

Fig. 3 is a schematic diagram of an apparatus and optical fibers set up for fabrication according to a further alternative embodiment of the present invention;

10 Fig. 4 is the view of Fig. 3 showing the fibers after fusion;

Fig. 5 is a view similar to that of Fig. 1 showing a further alternative embodiment of the present invention;

15 and  
Fig. 6 is a view of an adapter incorporating a still further attenuator fabricated according to the method of the present invention.

### 20 IV. DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to Fig. 1, optical fibers 10 and 12 are shown in preparation for fusion according to the method of the present invention. Each of fibers 10,12 include a signal transmitting core 14,16 surrounded by a cladding 18,20. The fibers terminate at terminal ends 22,24. The fibers 10,20 are of commercial construction and have an outside diameter  $D_0$  of about .125 millimeters. The cores of each of the fibers have a diameter  $D_c$  of about .010 millimeters for single mode fibers and about .050 millimeters for multi-mode fibers. The fibers 10,12 are connected to signal sources and receivers (not shown) such that an optical signal can be sent through the fibers 10,12 and the transmission loss through the fibers 10,12 can be measured during the method of the present invention.

35 As shown in Fig. 1, the fibers 10,12 are disposed in parallel side-by-side abutting and overlapping relation.

Specifically, as shown in Fig. 1, the axis X-X of fiber 10 is disposed in parallel and spaced apart alignment from the axis Y-Y of fiber 12. The cladding 18 of fiber 10 abuts the cladding 20 of fiber 12. As a result, the  
5 fibers cooperate to define an overlapped portion 26 having a length  $D_1$  which, in a preferred embodiment, is about .5 millimeters.

As shown in Fig. 1, the overlapped portion 26 is disposed between the electrodes 28,30 of an electrical  
10 arc generator. The complete generator is not shown and is a commercially available item to produce an arc between electrodes 28,30. In a preferred embodiment, the generator will produce an arc having a current flow of about .05 to .06 amps between electrodes 28,30. The  
15 arc produced by the electrodes 28,30 is an energy source for fusing the fibers, as will be described. It will be appreciated by those skilled in the art that any energy source could be used. Examples of alternative energy sources would be lasers or other heat sources.

20 In the method of the present invention, the electrodes 28,30 are energized to create a pulse arc of about one second duration to apply energy to the overlapped portion 26. By reason of the application of this energy, the cladding 18,20 partially melt and fuse  
25 together as shown in Fig. 2, such that the fibers 10,20 are now joined by a fused overlapped portion 26a.

After the initial fusion, the amount of signal transmission loss through the now coupled fibers 10,12 is measured. If the transmission loss is greater than a  
30 desired loss for an attenuator to be produced according to the present fabrication technique, a subsequent application of energy is supplied to portion 26a by passing a further arc between electrodes 28,30. The subsequent application of energy causes further fusing  
35 of the overlapped portion 26a. As a result of this further fusing, the cores 14,16 in region 26a move closer together resulting in reduced transmission loss.

Accordingly, multiple fuses results in the cores 14,16 moving progressively together with a resulting progressive decrease in the amount of transmission loss through the fibers 10,12.

5 As a result, the method of the present invention, includes application of energy to the overlapped portion 26 to at least partially fuse the fibers 10,12 in the overlapped portion 26. Following the application of energy, transmission loss through the fibers 10,12 is  
10 measured. If the transmission loss is greater than a desired transmission loss, subsequent applications of energy are applied. After each application of energy, the transmission loss through the fibers 10,12 is measured. The subsequent applications of energy  
15 followed by subsequent measurements of the transmission loss is continued until a desired transmission loss is attained.

From the foregoing, it can be seen how an attenuator of varying transmission losses can be attained. For  
20 example, transmission losses of 12,15 or 20 dB (or any other dB greater than 10dB) can be attained simply by controlling the amount or number of applications of energy to the overlapped portion 26.

The foregoing preferred embodiment is adequate for  
25 producing attenuators having transmission losses of greater than or equal to 10 dB. With reference to Figs. 3 and 4, an alternative embodiment to the present invention is shown for fabricating attenuators having losses less than 10 dB (but normally greater than 5 dB).

30 In Fig. 3, fibers 10',12' are shown. It will be appreciated that fibers 10',12' are identical in every respect to fibers 10 and 12 of Figs. 1 and 2. Accordingly, a detailed description of fibers 10' and 12' will not be given. The reader will note that the  
35 elements of fibers 10' and 12' are numbered identically to those of fibers 10 and 12 with the addition of apostrophes or prime designations.

Fibers 10',12' are held in anchors 40,42 which include threaded shafts 41,43 carried on platforms 44,46. As a result, anchors 40 and 42 may be raised or lowered relative to platforms 44,46. It will be appreciated that anchors for holding optical fibers 10',12' form no part of this invention per se. Such anchors are schematically shown in U.S. Patent No. 4,557,556 and U.S. Patent No. 4,557,557.

The anchors 40,42 firmly grip the fibers 10',12' and are spaced from the terminal ends 22',24' by a distance of about  $2\frac{1}{2}$  centimeters. In the embodiment of Fig. 3, the anchors 40,42 are initially placed such that the fibers 10',12' are disposed in side-by-side abutting relation to define an overlapped portion 26' having a preferred length  $D_2$  of about .35 millimeters. The overlapped portion 26' is positioned between the electrodes 28,30. As shown in Fig. 3, the axis of X'-X' and Y'-Y' of the fiber cores 14',16' are disposed in parallel and offset relation at the location of the anchors 40,42.

The electrodes 28,30 are energized and the energy of the arc flowing between the electrodes 28,30 causes melting of the claddings 18',20' in the overlapped portion 26'. While the cladding 18',20' in the overlapped portion 26' is in a semi-liquid state, the anchors 40,42 are moved relative to one another to bring the axes X'-X' and Y'-Y' in the region of anchor locations 40,42 to be in axial alignment. (Alternately, the fiber axis X'-X' and Y'-Y' may be aligned before the arc is applied). In Fig. 3, anchor 40 is indicated by arrow A as moving in an upward direction. Anchor 42 is indicated by arrow B to be moving in a downward direction. It will be appreciated that both of anchors 40 and 42 need not be moved. All that is required is that one of the anchors 40,42 moves relative to the other anchor to cause the axes X'-X' and Y'-Y' in the region of the anchors 40,42 to be in axial alignment.

The method described above results in a fused attenuator as shown in Fig. 4. As indicated in Fig. 4, the axes X'-X' and Y'-Y' are shown in axial alignment. We have found that this fabrication method permits  
5 fabrication of an attenuator of less than 10 dB. To further reduce the loss through the attenuator, subsequent applications of energy can be applied to the region 26a' to further move the cores 14',16' closer together. After each application of energy, the  
10 transmission loss through the fibers 10',12' is measured until the desired attenuator loss is achieved. We have found that the fiber cores 14,16 at overlapping section 26 approach one another and that attenuators having a loss of as low as 5 dB are attainable with the present  
15 technique.

Referring now to Fig. 5, a still further embodiment of the present invention is shown. In Fig. 5, fibers 10'' and 12'' are shown having cores 14'',16'' surrounded by claddings 18'' and 20''. The fibers 10''  
20 and 12'' are identical to fibers 10 and 12 except that at the terminal ends 22'',24'' fibers are provided with a reduced diameter portion in the form of a tapered areas 21'' and 23'' which taper the diameter of the cladding 18'',20'' from the full diameter  $D_0$  to a reduced  
25 diameter  $D_R''$ . In a preferred embodiment, the reduced diameter  $D_R''$  is about 0.5 millimeters. The length of the taper 23'' is about 2 millimeters.

As shown in Fig. 5, the fibers 10'' and 12'' are positioned similar to that of fibers 10 and 12 with the  
30 tapered portion 21'',23'' disposed in overlapping relation to define the overlapped portion 26''. The overlapped portion 26'' is then positioned between electrodes 28,30 and energy is applied to the overlapped portion 26'' to partially fuse the fibers 10'',12''.  
35 After application of the energy, the amount of attenuation is measured and subsequent applications of energy followed by subsequent measurements are performed



until desired attenuation is reached. Using the embodiment shown in Fig. 5, it is believed that attenuations as low as 1 dB can be obtained.

Fig. 6 shows a preferred use of an attenuator technique according to the present invention. In Fig. 5 6, an adapter 50 is shown. The adapter contains fibers 10 and 12 which have been fused at a fused portion 26a to achieve a desired amount of attenuation. Each of the fibers 10,12 are retained in axially aligned ceramic 10 ferrules 52,54. The ferrules are contained within a housing 56 which includes a first mating portion 58 and a second mating portion 60.

The adapter shown in Fig. 6 is suited for use with so called D4 connectors. D4 connectors are well known 15 in the art and form no part of this invention per se.

The attenuator 50 may be an in-line attenuator. Namely, by producing an attenuator according to the present invention, the attenuator 50 can have any one of a plurality of selected attenuation levels. A user can 20 simply select an attenuator 50 having a desired attenuation level and couple it with a fiber optic line to input a desired attenuation into the optical transmission line. Further, attenuators 50 having varying levels of attenuation can be connected to one 25 another having an additive effect on their attenuation levels.

From the foregoing detailed description of the present invention, it has been shown how the objects of the invention have been attained in the preferred 30 manner. However, modifications and equivalence of the disclosed concepts, such as those which readily occur to one skilled in the art, are intended to be included within the scope of the claims which are appended hereto.

What is claimed is:

1. A method for fabricating an optical attenuator from  
at least a first and a second optical fiber having  
5 first and second cladding, respectively, surrounding  
first and second cores, respectively, said method  
comprising the steps of:  
  
placing said first and second fibers in closely-  
10 spaced overlapping relation to define an overlapped  
portion of said fibers; and  
  
initially applying energy to said overlapped portion  
to at least partially fused said first and second  
15 fibers at said overlapped portion.
2. A method according to claim 1 wherein said placing  
step includes disposing said fibers in side-by-side  
abutting relation at said overlapped portion.
- 20 3. A method according to claim 1 wherein said placing  
step includes placing said fibers in parallel  
alignment at said overlapped portion.
- 25 4. A method according to claim 1 further comprising  
initially measuring an attenuation through said  
overlapped portion after said initial application of  
said energy.
- 30 5. A method according to claim 4 further comprising  
applying an additional application of energy to said  
overlapped portion after said initial measuring and  
measuring said attenuation after said additional  
application.
- 35 6. A method according to claim 5 further comprising  
performing subsequent additional applications of

SUBSTITUTE SHEET

energy to said overlapped portion followed by subsequent additional measurement of said attenuation until a measured attenuation achieves a desired attenuation.

5

7. A method according to claim 1 wherein said placing step includes placing a first and second anchor location of said first and second fibers, respectively, in relative positioning with axes of said first and second cores offset at said first and second anchor locations; and urging said first and second cores at said first and second anchor locations toward an axial alignment.

10

8. A method according to claim 1 comprising forming a reduced diameter portion on at least one of said first and second claddings and, in said placing step, positioning said reduced diameter portion at said overlapped portion.

20

9. A method according to claim 1 comprising applying said energy to move said cores toward one another.

SUBSTITUTE SHEET

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6



## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 92/07247

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>6</sup>		
According to International Patent Classification (C) or to both National Classification and IPC		
Int.Cl. 5 G02B6/26; G02B6/28		
<b>II. FIELDS SEARCHED</b>		
Minimum Documentation Searched <sup>7</sup>		
Classification System	Classification Symbols	
Int.Cl. 5	G02B	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched <sup>8</sup>		
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup></b>		
Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
Y	DE,A,3 042 587 (LICENTIA) 1 April 1982	1-3
A	see claims; figures ---	4-9
Y	EP,A,0 404 587 (FUJIKURA) 27 December 1990	1-3
	see claims; figures ---	
A	GB,A,2 088 578 (SSD) 9 June 1982	1
	see claims; figures ---	
A	EP,A,0 411 350 (JAE) 6 February 1991	1
	see claims; figures ---	
	-/--	
<p><sup>10</sup> Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p>		
<b>IV. CERTIFICATION</b>		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
19 NOVEMBER 1992	30. 11. 92	
International Searching Authority.	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	PFAHLER, R. 	

Form PCT/ISA/210 (second sheet) (January 1985)

## III. DOCUMENTS CONSIDERED RELEVANT (CONTINUED FROM THE SECOND SHEET)

Category <sup>a</sup>	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
A	US,A,4 557 557 (R.F.GLEASON) 10 December 1985 cited in the application see claims; figures ---	1
A	EP,A,0 144 136 (ATT) 12 June 1985 cited in the application see claims; figures ---	1
A	GB,A,2 140 167 (ATT) 21 November 1984 cited in the application see claims; figures -----	1



ANNEX TO THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO.

US 9207247  
SA 64246

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 19/11/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-3042587	01-04-82	None	
EP-A-0404587	27-12-90	JP-A- 3024506 JP-A- 3055505 US-A- 5058979	01-02-91 11-03-91 22-10-91
GB-A-2088578	09-06-82	None	
EP-A-0411350	06-02-91	JP-A- 3063609 CA-A- 2020470 US-A- 5069518	19-03-91 01-02-91 03-12-91
US-A-4557557	10-12-85	None	
EP-A-0144136	12-06-85	US-A- 4557556 CA-A- 1252633 DE-A- 3469015 JP-A- 60111202	10-12-85 18-04-89 03-03-88 17-06-85
GB-A-2140167	21-11-84	US-A- 4529262 CA-A- 1214058 DE-A- 3417164 FR-A- 2545946 JP-A- 59211002	16-07-85 18-11-86 06-12-84 16-11-84 29-11-84

EPO FORM P0079

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**